



SN 10/649,886
Pocket No. S-100,658
In Response to Office Action dated November 10, 2004

AMENDMENTS TO THE CLAIMS:

Please cancel claims 17-20 and 29-32. This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (original) A method for monitoring the composition of a fluid flowing through a vessel which comprises the steps of:
 - (a) applying a continuous periodic acoustical signal to the outside of the vessel such that the acoustical signal is transferred to the flowing fluid, thereby generating vibrational resonance features having a plurality of maxima and minima therein;
 - (b) detecting the vibrational features generated in the flowing liquid;
 - (c) sweeping the continuous periodic acoustical signal through a chosen frequency range which includes two chosen consecutive maxima among the vibrational resonance features; and
 - (d) measuring the frequency difference between the two chosen consecutive maxima of the flowing fluid.
2. (original) The method as described in claim 1, further comprising the step of determining the full-width-at-half-maximum of at least one of the two chosen consecutive resonance features.
3. (original) The method as described in claim 1, further comprising the step of determining the acoustic impedance of the fluid.
4. (original) The method as described in claim 1, further comprising the step of determining the ratio of the resonance feature minimum to the resonance feature maximum .
5. (original) An apparatus for monitoring the composition of a fluid flowing through a vessel which comprises in combination:
 - (a) a first transducer in acoustic contact with the outside surface of said vessel for applying a continuous periodic acoustical signal to the outside of said vessel such that the acoustical signal is transferred to said flowing fluid, thereby generating vibrational

SN 10/649,886
Docket No. S-100,658
In Response to Office Action dated November 10, 2004

resonance features having a plurality of maxima and minima therein;

- (b) a second transducer in acoustic contact with the outside of said vessel and located on the side thereof opposite to said first transducer for detecting the vibrational resonance features generated in the flowing liquid;
- (c) a sweep generator for sweeping said first transducer through a chosen frequency range which includes two chosen consecutive maxima among the vibrational resonance features; and
- (d) a data processor for determining the frequency difference between the two chosen consecutive maxima of the flowing fluid.

6. (original) The apparatus as described in claim 5, wherein said data processor determines the line width of at least one of the two chosen consecutive resonance features.

7. (original) The apparatus as described in claim 5, wherein said data processor determines the acoustic impedance of the fluid.

8. (original) The method as described in claim 5, wherein said data processor determines the ratio of the resonance feature minimum to the resonance feature maximum.

9. (original) An apparatus for monitoring the composition of a fluid flowing through a vessel which comprises in combination:

- (a) a first transducer in acoustic contact with the outside surface of said pipe for applying a continuous periodic acoustical signal to the outside of said vessel such that the acoustical signal is transferred to said flowing fluid, thereby generating vibrational resonance features having a plurality of maxima and minima therein, and for detecting the generated vibrational resonance features;
- (b) a sweep generator for sweeping said first transducer through a chosen frequency range which includes two chosen consecutive maxima in the vibrational resonance features; and

SN 10/649,886

Docket No. S-100,658

In Response to Office Action dated November 10, 2004

- (c) a data processor for recording the frequency difference between the two chosen consecutive maxima of the flowing fluid.

10. (original) The apparatus as described in claim 9, wherein said data processor determines the line width of at least one of the two chosen consecutive resonance features.

11. (original) The apparatus as described in claim 9, wherein said data processor determines the acoustic impedance of the fluid.

12. (original) The apparatus as described in claim 9, wherein said data processor determines the ratio of the resonance feature minimum to the resonance feature maximum.

13. (original) An apparatus for monitoring the composition of a fluid flowing through a vessel which comprises in combination:

- (a) a first transducer in acoustic contact with the outside surface of said vessel for applying a continuous periodic acoustical signal to the outside of said vessel such that the acoustical signal is transferred to said flowing fluid, thereby generating vibrational resonance features having a plurality of maxima and minima therein;
- (b) a second transducer in acoustic contact with the outside of said vessel and located on the same side thereof as said first transducer and in the vicinity thereof, for detecting the vibrational resonance features generated in the flowing liquid;
- (c) a sweep generator for sweeping said first transducer through a chosen frequency range which includes two chosen consecutive maxima among the vibrational resonance features; and
- (d) a data processor for determining the frequency difference between the two chosen consecutive maxima of the flowing fluid.

14. (original) The apparatus as described in claim 13, wherein said data processor determines the line width of at least one of the two chosen consecutive resonance features.

SN 10/649,886

Docket No. S-100,658

In Response to Office Action dated November 10, 2004

15. (original) The apparatus as described in claim 13, wherein said data processor determines the acoustic impedance of the fluid.

16. (original) The apparatus as described in claim 13, wherein said data processor determines the ratio of the resonance feature minimum to the resonance feature maximum.

17-32. (cancelled)